

Tolex

SHEETS
DISCS

Patented



Speed Of Dry, Finishes Like Wet. Tolex, The Perfect System For Your Topcoat Sanding.



Tolex, a breakthrough in both micro-finishing sanding and dry lubrication process technology, results in a system that allows true topcoat sanding without the use of water. Dust nibs can now be located and removed quickly thanks to the blocking effect of the Tolex pads. Tolex scratches are extremely uniform and shallow, they can be easily removed by light compounding or with the Buflex system.



If you are concerned with the productivity of your topcoat finishing but prefer not to wet sand, Tolex finishes are the closest to wet but with the speed of dry sanding.



Achieving quality through consistency.
Manufactured by Kovax Corporation, Japan

Tolex The Best Finish In Dry Topcoat Sanding!

Utilizing the most uniform abrasive minerals available and state of the art Roller Coating technology, Tolex system achieves finishes more evenly and shallower than any other dry sanding system in similar finish. Its highly effective dry lubrication process allows minimum clogging, thus increasing sanding life and productivity.

Advantages:

- Finest Topcoat Sanding
- Extremely Uniform Finish
- Minimum Clogging, Longer Lasting
- Finish Equivalent: **>P1500 (Manual)**
>P2000 (Machine)



STICKON

TOLEX Stickon Discs & Sheets (Blocking Effect)

Topcoat sanding will be faster and more efficient as small paint runs and dust nibs are easily identified and located in the first pass of light sanding with Tolex. These imperfections are then quickly and effectively removed by continued sanding on needed areas only. Therefore, oversanding as well as overlooked dust nibs can be easily avoided.



Part No.	Description	Size	Pcs per Unit
191-1503	Tolex Stickon Sheets	114 x 70 mm	25
971-0016	Tolex Pads	110 x 67 mm	2
192-1503	Tolex Stickon Discs	6" dia.	25
971-0017	Tolex Disc Pads	6" dia.	2

Super TOLEX Discs & Sheets (Flexible)

Velour backing Tolex sheets are ideal for light topcoat sanding in removing minor over-runs and small dust nibs. Highly effective dry lubrication process allows minimum clogging, thus increasing sanding life and productivity. Due to its extreme flexibility, Super Tolex can sand both the inside valleys and peaks of Orange Peel with minimum removal.

Part No.	Description	Size	Pcs per Unit
191-1533	Tolex SUPER-TACK Discs	170 x 130 mm	25
971-0035	Interface Pads	120 x 75 mm	4
00212	Foam Block	120 x 65 mm	1
730-1502	Tolex SUPER-TACK Discs	3" dia.	50
971-7502	Extra-Soft Cushion Pads	3" dia.	4
193-1503	Tolex SUPER-TACK Discs	6" dia.	25
971-0042	Interface Pads for Normal Use	6" dia.	2
971-7052	Extra-Soft Cushion Pad	6" dia.	1



SUPER-TACK

SUPER-TACK = Hook & Loop

Recommended Air Tools



P/N 910-0202

Part No.	Description	Weight	Speed	Orbit Diameter	Air Consumption	Air Pressure
910-0202	BA Sander	1.60 lbs	8,500 rpm	3 mm	12.0 CFM	58-87 psi
910-0603	PROMA-X 6" DA Sander	1.90 lbs	12,000 rpm	5 mm	17.0 CFM	90 psi
910-0102	6" DA Sander	1.98 lbs	10,000 rpm	5 mm	13.4 CFM	57-87 psi



P/N 910-0603